

# Video Security

Monitors | eneo CRT Monitors

## VMC-21/1

21"(53cm) Colour Monitor, Composite, Y/C, Audio Inputs, 500TVL

Art-No. 90442



## Features

**21" High Resolution Picture Tube**  
**Resolution of 500 Horizontal Lines**  
**Automatic PAL/NTSC Selection**  
**Video / Audio Loop-through Inputs**  
**Over / Underscan Function**

**Built-in Comb Filter**  
**Built-in Loudspeaker**  
**Universal Voltage Input: 100 to 240VAC, 50/60 Hz**  
**Detachable Power Cord**  
**Rugged Metal Housing**

## Specifications

<b>Picture tube type (CRT)</b>	90° In-line flatscreen tube (0.74mm DOT pitch)
<b>Screen size</b>	21" (53cm)
<b>Video standard</b>	PAL/NTSC
<b>PAL/NTSC signal selection</b>	Automatic
<b>Scanning frequency range H/V</b>	15625 / 50Hz, 15750 / 60Hz
<b>Horizontal resolution</b>	450 TV lines
<b>Video inputs</b>	2x 1Vp-p, CVBS, (loop-through), automatic 75ohms termination, Y/C input, 4-pin Mini DIN, 75ohm (loop-through)
<b>Audio inputs</b>	2x 300mVrms, Cinch (loop-through)
<b>Connectors</b>	2x Video and audio loop-through inputs (BNC/Cinch), Y/C loop-through input (4-pin Mini DIN), Power input
<b>Synchronization</b>	Internal
<b>Audio output power</b>	2watts
<b>Over-/Underscan</b>	7% / 3%
<b>LED indication</b>	Sources selected, Power ON/OFF
<b>Operations (Front part)</b>	On-screen menu, Menu selection, Input selectors, Over/Underscan button, Power ON/OFF
<b>Operations (back part)</b>	None
<b>Supply voltage</b>	100 to 240AC, 50/60Hz

(Specifications continued)

<b>Power consumption</b>	80watts
<b>Temperature range</b>	0°C to +40°C
<b>Housing</b>	Steel (with plastic front)
<b>Colour</b>	Pantone Coolgrey 7C
<b>Dimensions (HxWxD)</b>	450x490x478mm
<b>Weight</b>	27.5kg
<b>Special features</b>	Automatic 75ohms termination on not-used BNC loop-through inputs, Detachable power cord